

KLAMFLEX REPAIR CLAMPS

- ❑ Klamflex Repair Clamps (KRC) are designed with a UNIQUE 2 STAGE sealing arrangement to provide a repair means for small leaks in Steel, PVC, HDPE, DI & AC pipelines.
- ❑ The UNIQUE 2 STAGE sealing arrangement provides superior sealing capabilities enabling leaking pipes to be repaired more effectively and efficiently on site.
- ❑ Klamflex uses only 16 REPAIR CLAMPS to accommodate pipe outside diameters from 48 to 380mm, making stocking more economical.
- ❑ The KRC is rated to a maximum working pressure of 16 bar for pipe outside diameters of less than 234mm and 12 bar for pipe outside diameters over 234mm.



REPAIR CLAMPS - SIZE RANGE

NB (mm)	RANGE (mm)	WIDTH (mm)	WIDTH (mm)	WIDTH (mm)	WIDTH (mm)
		150mm	200mm	300mm	400mm
40-50	48-63	x			
65	69-84	x			
80	89-104	x			
100	110-125	x			
125	140-155		x		
150	160-175		x		
150	177-192		x		
200	196-211		x		
200	219-234		x		
200-225	239-254			x	
225-250	262-277			x	
250	284-299			x	
250-300	304-319			x	
300	324-340				x
350	345-360				x
350	365-380				x

MATERIALS OF CONSTRUCTION

STRAP	304SS
RUBBER	SBR SANS 4633:2008
CLAMP END	DUCTILE IRON BSEN 1563:1997
COATING	FUSION BONDED EPOXY BSEN 6920 WRAS
BOLTS/NUTS/WASHERS	4.6 EG BSEN 12329:2000/BSEN 12330:2000

